

## **ECODESIGN REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS** ACCORDING TO COMMISSION REGULATION (EU) 2015/1185 IMPLEMENTING DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Model Identifier(s):	VIOLA EVO	
Indirect heating functionality:	no	
Direct heat output:	12,1	

\_

Indirect heat output:

Fuel	Preferred fuel (only	$\eta_{s}$ [%]:	emi	Space heating emissions at nominal heat output (*)			Space heating emissions at minimum heat output (*) (**)				
Fuei	one):		۱ <sub>Is</sub> [ /oj.	PM	OGC	со	NO <sub>x</sub>	PM	OGC	со	$NO_{\rm x}$
		F	m	g/Nm <sup>3</sup>	(13%0	D <sub>2</sub> )	m	g/Nm <sup>3</sup>	(13%0	<b>D</b> <sub>2</sub> )	
Wood logs with moisture content ≤ 25 %	yes	no	77	11	24	387	78	-	-	-	-
Compressed wood with moisture content < 12 %	no	no									
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminus coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									





## Characteristics when operating with the preferred fuel only:

onaracteristics when open				y.
Item	Symbol	Value	Unit	Item Symbol Value Unit
Heat output				Useful efficiency (NCV as received)
Nominal heat output	P <sub>nom</sub>	12,1	kW	Useful efficiency at nominal heat output 96,7 %
Minimum heat output (indicative)	P <sub>min</sub>	-	kW	Useful efficiency at minimum heat output η <sub>th,min</sub> - % (indicative)
Auxiliary elettricity consun	nption		·	Type of heat output/room temperature control (sel one)
At nominal heat output	el <sub>max</sub>	-	kW	single stage heat output, no room no no
At minimum heat output	el <sub>min</sub>	-	kW	two or more manual stages, no no no
In standby mode	el <sub>SB</sub>	-	kW	with mechanic thermostat room no no
Permanent pilot flame pow	er require	ement		with eletronic room tempearture no
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	n.p.	kW	with eletronic room tempearture no
				with eletronic room tempearture no
				Other control options (multiple selections possible
				room temperature control, with no no
				room temperature control, with open window detection no
				with distance control option no
Contact details	Name a	nd addre	ess of the	anufacturer or its authorised representative
+39 0445 741310 +39 0445 741657 info@thermorossi.it			1/:	
www.thermorossi.com				rumulo, 4 - 36011 Arsiero (VI) - IT
(*) PM – particulate matter (	DGC = org	-		ds, CO = carbon monoxide, $NO_x$ = nitrogen oxides
(**) Only required if correctio	n factors I	-(2)  or  F(3)	s) are appi	
	n factors I	-(2) or F(3	s) are appi	
(**) Only required if correctio	n factors I	-(2) or F(3	are appi	

Technical report ref. 2004694/01

Approved by Maurizio Lorenzon Industry Division Manager

Kiwa Cermet Italia S.p.A. Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl Sede legale: Via Cadriano 23, 40057 Granarolo dell'Emilia (BO) Tel. +39.051.459.3.111 - Fax +39.051.763.382 - info@kiwacermet.it - www.kiwacermet.it Pl. 00627711203 - C.F. 03502820370 - Capitale Sociale: € 1.000.000,00 i.v.